



TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks, block heater, battery charger and external fuel connect.

STANDARD FEATURES ON ALL RENTAL MODELS

- ❖ DEEP SEA CONTROLLER
- ❖ CAMLOCKS
- ❖ BLOCK HEATER
- ❖ BATTERY CHARGER
- ❖ EXTERNAL FUEL CONNECT
- ❖ DISTRIBUTION PANEL WITH RECEPTACLES
- ❖ WATER SEPARATOR FILTER



▪ True 120V 20A outlet available in all phases.

▪ The engine

▪ Camlocks are standard on all units.



ENERMAX SERIES

Prime 39kW | Standby 43kW

KL50 TSX		
SERIES		ENERMAX
GENERATOR SPECS		
Prime Power (PRP)	kW	39,0
Prime Power (PRP)	kVA	48,8
Standby Power (LTP)	kW	43,0
Standby Power (LTP)	kVA	53,8
Rated Power Factor (cos φ)		0,8
RPM		1800
Voltage 1PH	V	240/120V
Voltage 3PH	V	480/277V 208/120V
Rated frequency	Hz	60
Controller Brand		Deep Sea
Controller Model		DSE7310
Sound Level @23 Feet (no load)	dB	69
AMPS		
Single Phase 120V zz		125x2 zz
Single Phase 240V		125
Three Phase 208V		135
Three Phase 480V		59
GENERAL ENGINE DATA		
Engine brand		Kohler
Engine model		KDI2504TCR
EPA LEVEL		TIER4 FINAL
Cylinders	no.	4
R.P.M.	rpm	1800
Gross Horse power	HP	59,4
External fuel Valve		Yes
Fuel Containment	%	110%
FUEL CONSUMPTION		
Fuel Type		Diesel
Fuel Capacity	gal.	71
Fuel Cons. at 75% (P.R.P.)	gal/h	2,01
Run Time @ 75%	gal/h	35,32
DEF		
DEF Tank Capacity	gal.	N/A



69
dBA
@ 23 Feet



ALTERNATOR DATA		
Alternator brand		Leroy Somer
Alternator model		LSA 42.3M7
P.R.P. Power	kVA	50
L.T.P. Power	kVA	55
IP Protection		23
Voltage regulator		±0,25% AREP
Short-circuit current		300 %: 10s
WEIGHTS AND DIMENSIONS SKID WITH TRAILER		
Length	in.	160
Width	in.	74
Height	in.	74
Dry weight		4069
Wet weight	lbs.	4573

WEIGHTS AND DIMENSIONS SKID WITHOUT TRAILER		
Length	in.	91
Width	in.	44
Height	in.	67,3
Dry weight		3025
Wet weight	lbs.	3421

NOTICE

Generator is not intended for use in enclosed areas or where free flow of air is restricted. Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.