

**ENERPACK SERIES**

**ZERO EMISSION**



**ENERPACK SERIES**



For example purposes only


**KEY FEATURES**

- Up to more than 350% overload capacity for 300 seconds
- Parallel capability standard
- Digital control panel
- Distribution panel with camlocks and service outlets
- Canopy made of galvanized steel
- Recessed central lifting hook
- 4 Lifting eyes
- Forklift guides on every side
- Two levels stackable
- EV charger DC CCS1 and AC TYPE1 as option

**POWER SOURCES**




PHOTOVOLTAIC



WIND ENERGY



POWER GENERATORS



GRID

**APPLICATIONS**



UPS



CONSTRUCTION






DISASTER RELIEF



EVENTS

## ENERPACK SERIES

**ZERO EMISSION** 

ENERPACK BESS 40/100T US L		
THREE PHASE / 60 Hz		
GENERAL TECHNICAL DATA	Units	EP 40 / 100 T US L
Three phase Voltage	VAC	208
Single phase Voltage	VAC	120
Frequency	Hz	60
Nominal Energy Storage	kWh	129
Continuous load at power factor = 0.8	kVA	40
Overload (300 seconds) <sup>1</sup>	kW	120
Communication technology		CAN bus
Sound Power Level	dB(A)	< 55 dB(A)@23'
Protection degree		IP44
Phases		3 PHASE
Operation Temperature	°F	-4 °F to +113 °F <sup>2</sup>
BATTERY		
Brand		
Quantity	units	8
Battery Voltage	VDC	179.2
Operating Voltage	VDC	716.8
Lithium cell chemistry		<b>LiFePO4</b>
Discharge current		1 C
DOD % (depth of discharge @25°C ±3)		0.8
Cycle Life <sup>3</sup>		> 6000
Manufacturing Country		ITALY
INVERTER		
Brand		
Quantity	units	1
Continuous load at power factor = 0.8	kVA	40
Nominal Power	kW	32
Accepted peak load @ 400V (300 sec)	kW	150 (4.68Pn)
Manufacturing Country		ITALY
CONTROL		
Energy Management system (EMS)		ComAp
Battery management system (BMS)		Hermes M3
Brand		
Manufacturing country		ITALY
DIMENSIONS AND WEIGHT		
Dimensions (L x W x H) <sup>4</sup>	in	110.8x44.8x75.6
Weight <sup>4</sup>	lb	9488
OPTIONS		
Air Conditioning System		on request
Fire Extinguishing System		-
Solar Battery Charger		on request
Air filtration panels		on request
EV Charger DC CCS1		on request
EV Charger AC Type1		on request

<sup>1</sup> Up to SOC of 50%

<sup>2</sup> For temperatures > 113 °F Air Conditioning System is available as option

<sup>3</sup> With reduced DOD

<sup>4</sup> Dimensions may vary depending on the options added

Technical data not binding