

ENERPACK SERIES





For example purposes only

KEY FEATURES

- □ Up to more than 350% overload capacity for 300 seconds
- Parallel capability standard
- Digital control panel
- Distribution panel with camlocks and service outlets
- **■** 40'Container
- ☐ 4-point lift
- Forklift guides
- EV charger DC CCS1 and AC TYPE1 as option

POWER SOURCES



PHOTOVOLTAIC



WIND **ENERGY**



POWER GENERATIORS



GRID

APPLICATIONS



UPS



CONSTRUCTION





RELIEF

DISASTER **EVENTS**



100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com (855) 303-7900

RPACK SERIE

Fax (302) 231-1162

sales@ftgequipment.com

ZERO ENISSION



ENERPACK SERIES

ENERPACK BESS 480/2000T US N		
THREE PHASE / 60 Hz		
GENERAL TECHNICAL DATA	Units	EP 480 / 2000T US N
Three phase Voltage	VAC	480
Single phase Voltage	VAC	277
Frequency	Hz	60
Nominal Energy Storage	kWh	2016
Continuos load at power factor = 0.8	kVA	480
Overload (300 seconds) ¹	kW	1400
Comunication technology		CAN bus
Sound Power Level	dB(A)	< 55 dB(A)@23'
Protection degree		IP44
Phases		3 PHASE
Operation Temperature	°F	-4 °F to +113 °F ²
BATTERY		
Brand		archimede energia
Quantity	units	108
Battery Voltage	VDC	388.8
Operating Voltage	VDC	777.6
Lithium cell chemistry		LiNMC
Discharge current		2.9 C
DOD % (depth of discharge @25°C ±3)		0.8
Cycle Life ³		> 6000
Manufacturing Country		ITALY
INVERTER		
Brand		POWERTRONIX Uninterruptible Power Supply
Quantity	units	4
Continuos load at power factor = 0.8	kVA	120
Nominal Power	kW	96
Accepted peak load @ 400V (300 sec)	kW	350 (3.64 Pn)
Manufacturing Country		ITALY
CONTROL		
Energy Management system (EMS)		ComAp
Battery management system (BMS)		Hermes M3
Brand		archimede energia
Manufacturing country		ITALY
DIMENSIONS AND WEIGHT		
Dimensions (L x W x H) ⁴	in	40' container
Weight ⁴	lb	61597
OPTIONS		
Air Conditioning System		on request
Fire Extinguishing System		on request
Solar Battery Charger		on request
Air filtration panels		on request
EV Charger DC CCS1		on request
EV Charger AC Type1		on request

¹Up to SOC of 50%

Technical data not binding



² For temperatures > 113 °F Air Conditioning System is available as option

³ With reduced DOD

⁴ Dimensions may vary depending on the options added