

KL80 TSX

ENERMAX SERIES

Prime 65kW | Standby 71.5kW













TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks, block heater, battery charger and external fuel connect.



True 120V 20A outlet available in all phases.



 External fuel hook-ups are standard allowing for quick connection to additional fuel.



 Camlocks are standard on all units.

STANDARD FEATURES ON ALL RENTAL MODELS

- ❖ DEEP SEA CONTROLLER
- CAMLOCKS
- **❖** BLOCK HEATER
- BATTERY CHARGER
- EXTERNAL FUEL CONNECT
- DISTRIBUTION PANEL WITH RECEPTACLES
- ❖ WATER SEPARATOR FILTER





100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com (855) 303-7900

Fax (302) 231-1162 sales@ftgequipment.com



KL80 TSX

ENERMAX SERIES

Prime 65kW | Standby 71.5kW

KL80 TSX				
SERIES		ENERMAX		
GENERATOR SPECS				
Prime Power (PRP)	kW	65.0		
Prime Power (PRP)	kVA	81		
Standby Power (LTP)	kW	71.5		
Standby Power (LTP)	kVA	89.4		
Rated Power Factor (cos φ)		0.8		
RPM		1800		
Voltage 1PH	V	240/120V		
Voltage 3PH	V	480/277V 208/120V		
Rated frequency	Hz	60		
Controller Brand		Deep Sea		
Controller Model		DSE7310		
Sound Level @23 Feet (no load)	dB	69		
AMPS				
Single Phase 120V zz		217x2 zz		
Single Phase 240V		217		
Three Phase 208V		226		
Three Phase 480V		98		
GENERAL ENGINE DATA				
Engine brand		Kohler		
Engine model		KDI3404TCR		
EPA LEVEL		TIER4 FINAL		
Cylinders	no.	4		
R.P.M.	rpm	1800		
Gross Horse power	HP	100		
External fuel Valve		Yes		
Fuel Containment	%	110%		
FUEL CONSUMPTION				
Fuel Type		Diesel		
Fuel Capacity	gal.	79		
Fuel Cons. at 75% (P.R.P.)	gal/h	3.6		
Run Time @ 75%	hrs	21.94		
DEF				
DEF Tank Capacity	gal.	4.3		











ALTERNATOR DATA				
Alternator brand		Leroy Somer		
Alternator model		LSA 44.3S3		
P.R.P. Power	kVA	87		
L.T.P. Power	kVA	96		
IP Protection		23		
Voltage regulator		±0,25% AREP		
Short-circuit current		300 %: 10s		
WEIGHTS AND DIMENSIONS WITH TRAILER				
Length	in.	173		
Width	in.	74		
Height	in.	85		
Dry weight	lbs.	5458		
Wet weight	105.	6111		

WEIGHTS AND DIMENSIONS WITHOUT TRAILER				
Length	in.	100		
Width	in.	44		
Height	in.	70		
Dry weight	lbs.	3950		
Wet weight		4631		

NOTICE

Generator is not intended for use in enclosed areas or where free flow of air is restricted.

Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.

