

VO700 TSX

ENERMAX SERIES

Prime 560kW | Standby 617kW













TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks, block heater, battery charger and external fuel connect.



 True 120V 20A outlet available in all phases.



 External fuel hook-ups are standard allowing for quick connection to additional fuel.



 Camlocks are standard on all units.

STANDARD FEATURES

- PARALLEL STANDARD
- ❖ DEEP SEA CONTROLLER
- CAMLOCKS
- **❖** BLOCK HEATER
- **&** BATTERY CHARGER
- **❖** EXTERNAL FUEL CONNECT
- DISTRIBUTION PANEL WITH RECEPTACLES
- **❖** WATER SEPARATOR FILTER





100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com (855) 303-7900

Fax (302) 231-1162

sales@ftgequipment.com



VO700 TSX

ENERMAX SERIES

Prime 560kW | Standby 617kW

VO700TSX				
SERIES		ENERMAX		
GENERATOR SPECS				
Prime Power (PRP)	kW	560.0		
Prime Power (PRP)	kVA	700.0		
Standby Power (LTP)	kW	617.0		
Standby Power (LTP)	kVA	771.3		
Rated Power Factor (cos φ)		0.8		
RPM		1800		
Voltage 1PH	V			
Voltage 3PH	V	480/277V 208/120V		
Rated frequency	Hz	60		
Controller Brand		Deep Sea		
Controller Model		DSE8610		
Sound Level @23 Feet (no load)	dB	72		
AMPS				
Single Phase 120V zz				
Single Phase 240V				
Three Phase 208V		1943		
Three Phase 480V		842		
GENERAL ENGINE DATA				
Engine brand		VOLVO		
Engine model		TWD1683GE		
EPA LEVEL		TIER4 FINAL		
Cylinders	no.	6		
R.P.M.	rpm	1800		
Gross Horse power	HP	932		
External fuel Valve		Yes		
Fuel Containment	%	110%		
FUEL CONSUMPTION				
Fuel Type		Diesel		
Fuel Capacity	gal.	465		
Fuel Cons. at 75% (P.R.P.)	gal/h	28.12		
Run Time @ 75%	hrs	16.53		
DEF				
DEF Tank Capacity	gal.	42		











ALTERNATOR DATA				
Alternator brand		Leroy Somer		
Alternator model		LSA 47.3L10		
P.R.P. Power	kVA	715		
L.T.P. Power	kVA	785		
IP Protection		23		
Voltage regulator		±0,25% AREP		
Short-circuit current		300 %: 10s		
WEIGHTS AND DIMENSIONS WITH TRAILER				
Length	in.	261		
Width	in.	102		
Height	in.	115		
Dry weight	lbs.	20437		
Wet weight		23739		

WEIGHTS AND DIMENSIONS WITHOUT TRAILER				
Length	in.	191		
Width	in.	79		
Height	in.	93		
Dry weight	lbs.	17637		
Wet weight		21247		

NOTICE

Generator is not intended for use in enclosed areas or where free flow of air is restricted.

Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.

