

KL20 TSX

ENERMAX SERIES

Prime 16kW | Standby 16kW



TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 10kW to 1,000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks and external fuel connect.



True 120V 20A outlet .30 amp twistlockstandard.



 External fuel hook-ups are standard allowing for quick connection to additional fuel.



 Camlocks are standard on all units.

STANDARD FEATURES ON ALL RENTAL MODELS

- ✤ DEEP SEA CONTROLLER
- CAMLOCKS
- EXTERNAL FUEL CONNECT
- DISTRIBUTION PANEL WITH RECEPTACLES
- ✤ WATER SEPARATOR FILTER





100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com

(855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com



KL20 TSX

ENERMAX SERIES

Prime 16kW | Standby 16kW

KL20 TSX			
SERIES		ENERMAX	
GENERATOR SPECS			
Prime Power (PRP)	kW	16	
Prime Power (PRP)	kVA	20	
Standby Power (LTP)	kW	16	
Standby Power (LTP)	kVA	20	
Rated Power Factor (cos φ)		0.8	
RPM		1800	
Voltage 1PH	V	240/120V	
Voltage 3PH	V	480/277V 208/120V	
Rated frequency	Hz	60	
Controller Brand		Deep Sea	
Controller Model		DSE7310	
Sound Level @23 Feet (no load)	dB	67	
AMPS			
Single Phase 120V zz		67x2 zz	
Single Phase 240V		67	
Three Phase 208V		56	
Three Phase 480V		24	
GENERAL ENGINE DATA			
Engine brand		Kohler	
Engine model		KDI1903M	
EPA LEVEL		TIER4 FINAL	
Cylinders	no.	3	
R.P.M.	rpm	1800	
Gross Horse power	HP	24.7	
External fuel Valve		Yes	
Fuel Containment	%	110%	
FUEL CONSUMPTION			
Fuel Type		Diesel	
Fuel Capacity	gal.	44	
Fuel Cons. at 75% (P.R.P.)	gal/h	1.0	
Run Time @ 75%	gal/h	44	
DEF			
DEF Tank Capacity	gal.	N/A	





ALTERNATOR DATA			
Alternator brand		Leroy Somer	
Alternator model		LSA 40M5	
P.R.P. Power	kVA	22	
L.T.P. Power	kVA	24.5	
IP Protection		23	
Voltage regulator		±0,25% AREP	
Short-circuit current		300 %: 10s	
WEIGHTS AND DIMENSIONS WITH TRAILER			
Length	in.	101	
Width	in.	63	
Height	in.	75	
Dry weight	lbs.	1525	
Wet weight		1837	
WEIGHTS AND DIMENSIONS WITHOUT TRAILER			
Length	in.	69	
Width	in.	39	
Height	in.	59	
Dry weight	lbs.	1345	
Wet weight		1487	
NOTICE			

NOTICE

Generator is not intended for use in enclosed areas or where free flow of air is restricted.

Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.



100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com (855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com