

VO1250TSX

ENERMAX SERIES

Prime 1006kW | Standby 1104kW











TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks, block heater, battery charger and external fuel connect.



STANDARD FEATURES

- PARALLEL STANDARD
- ✤ DEEP SEA CONTROLLER
- CAMLOCKS
- BLOCK HEATER
- BATTERY CHARGER
- EXTERNAL FUEL CONNECT
- DISTRIBUTION PANEL WITH RECEPTACLES
- ✤ WATER SEPARATOR FILTER





100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com

(855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com



VO1250TSX

ENERMAX SERIES

Single Phase 120V zz Single Phase 240V

Three Phase 208V

Three Phase 480V

Gross Horse power

External fuel Valve

Fuel Containment

FUEL CONSUMPTION PER ENGINE

Fuel Cons. at 25% (P.R.P.)

Fuel Cons. at 50% (P.R.P.)

Fuel Cons. at 75% (P.R.P.)

Fuel Cons. at 100% (P.R.P.)

Fuel Capacity

Engine brand

Engine model **EPA LEVEL**

Cylinders

R.P.M.

DEF

GENERAL ENGINE DATA

VO1250TSX-40				
SERIES		ENERMAX		
GENERATOR SPECS				
Prime Power (PRP)	kW	1006.0		
Prime Power (PRP)	kVA	1257.5		
Standby Power (LTP)	kW	1104.0		
Standby Power (LTP)	kVA	1380.0		
Rated Power Factor (cos φ)		0.8		
RPM		1800		
Voltage 1PH	V			
Voltage 3PH	V	480/277V 208/120V		
Rated frequency	Hz	60		
Controller Brand		Deep Sea		
Controller Model		DSE8610 x 2		
Sound Level @23 Feet (no load)	dB	73		
AMPS				

3490

1513

VOLVO

TWD1683GE x 2

TIER4 FINAL

6

1800

811 x 2

Yes

110%

1109

12.19

19.99

28.12

36.92

42+42=84

no.

rpm

ΗP

%

gal

gal/h

gal/h

gal/h

gal/h

gal.

Prime 1006kW | Standby 1104kW





ALTERNATOR DATA				
Alternator brand		Leroy Somer		
Alternator model		LSA 47.3L9 x 2		
P.R.P. Power	kVA	661		
L.T.P. Power	kVA	728		
IP Protection		23		
Voltage regulator		±0,25% AREP		
Short-circuit current		300 %: 10s		
WEIGHTS AND DIMENSIONS WITH TRAILER				
Length	in.	480		
Width	in.	96		
Height	in.	162.00		
Dry weight	lbs.	50383		
Wet weight		58855		

WEIGHTS AND DIMENSIONS WITHOUT TRAILER				
Length	in.	40' high cube container		
Width	in.			
Height	in.			
Dry weight	lbs.	43783		
Wet weight		52255		

NOTICE

Generator is not intended for use in enclosed areas or where free flow of air is restricted.

Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.



DEF Tank Capacity

100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com

(855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com