

VO630 TSX

72 dba

-130°F

ENERMAX SERIES

Prime 503kW | Standby 552kW



TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler, Scania. Standard features include camlocks, block heater, battery charger and external fuel connect.



• True 120V 20A outlet available in all phases.



 External fuel hook-ups are standard allowing for quick connection to additional fuel.



 Camlocks are standard on all units.

STANDARD FEATURES

- PARALLEL STANDARD
- ✤ DEEP SEA CONTROLLER
- CAMLOCKS
- BLOCK HEATER
- BATTERY CHARGER
- EXTERNAL FUEL CONNECT
- DISTRIBUTION PANEL WITH RECEPTACLES
- ✤ WATER SEPARATOR FILTER





100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com

(855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com



VO630 TSX

ENERMAX SERIES

VO630TSX			
SERIES		ENERMAX	
GENERATOR SPECS			
Prime Power (PRP)	kW	503.0	
Prime Power (PRP)	kVA	629.0	
Standby Power (LTP)	kW	552.0	
Standby Power (LTP)	kVA	690.0	
Rated Power Factor (cos φ)		0.8	
RPM		1800	
Voltage 1PH	V		
Voltage 3PH	V	480/277V 208/120V	
Rated frequency	Hz	60	
Controller Brand		Deep Sea	
Controller Model		DSE8610	
Sound Level @23 Feet (no load)	dB	72	
AMPS			
Single Phase 120V zz			
Single Phase 240V			
Three Phase 208V		1745	
Three Phase 480V		756	
GENERAL ENGINE DATA			
Engine brand		VOLVO	
Engine model		TWD1683GE	
EPA LEVEL		TIER4 FINAL	
Cylinders	no.	6	
R.P.M.	rpm	1800	
Gross Horse power	HP	932	
External fuel Valve		Yes	
Fuel Containment	%	110%	
FUEL CONSUMPTION			
Fuel Type		Diesel	
Fuel Capacity	gal.	465	
Fuel Cons. at 75% (P.R.P.)	gal/h	28.12	
Run Time @ 75%	gal/h	16.53	
DEF			
DEF Tank Capacity	gal.	42	

Prime 503kW | Standby 552kW





ALTERNATOR DATA				
Alternator brand		Leroy Somer		
Alternator model		LSA 47.3L9		
P.R.P. Power	kVA	661		
L.T.P. Power	kVA	728		
IP Protection		23		
Voltage regulator		±0,25% AREP		
Short-circuit current		300 %: 10s		
WEIGHTS AND DIMENSIONS WITH TRAILER				
Length	in.	261		
Width	in.	102		
Height	in.	115		
Dry weight	lbs.	19952		
Wet weight	105.	23254		
WEIGHTS AND DIMENSIONS WITHOUT TRAILER				
Length	in.	191		
Width	in.	79		
Height	in.	93		
Dry weight	lbs.	17416		
Wet weight	IDS.	21026		
NOTICE				

Generator is not intended for use in enclosed areas or where free flow of air is

restricted.

Backfeed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device. Specifications are subject to change without notice.



100 Paper Place New Castle, DE 19720 www.TecnoGenUSA.com

(855) 303-7900 Fax (302) 231-1162 sales@ftgequipment.com